


CB-108 Series

8-port RS-232 PC/104-Plus modules



- > 921.6 Kbps maximum baudrate for super fast data transmission
- > On-chip H/W and S/W flow control
- > Built-in 15 KV ESD protection
- > Onboard Tx and Rx LED indicators for each port
- > Windows (XP/Vista/7), Windows CE 5.0/6.0, and Windows XP embedded operating systems supported
- > Wide temperature model available for -40 to 85°C environments



: Overview

The CB-108 PC/104-Plus modules come with 8 RS-232 ports, and can be used with PC/104-Plus CPU boards that accept the PC/104-Plus expansion interface. Optional DB9 and DB25 connection cables are available for connecting to serial devices, and the CB-108s'

versatile driver support makes the modules suitable for a wide range of applications. The CB-108 modules can be used on the PC/104-Plus (PCI) bus, and provide a reliable, high performance solution for multiport serial communication.

: Specifications

Hardware

Comm. Controller: MU860 (16C550C compatible)

Bus: PC/104-Plus bus

Connector: 40-pin box header

Serial Interface

Number of Ports: 8

Serial Standards: RS-232

Max. No. of Boards per PC: 4

Serial Line Protection

ESD Protection: 15 KV on the board

Performance

Baudrate: 50 bps to 921.6 Kbps

Serial Communication Parameters

Data Bits: 5, 6, 7, 8

Stop Bits: 1, 1.5, 2

Parity: None, Even, Odd, Space, Mark

I/O Address: Assigned by BIOS

IRQ: Assigned by BIOS

FIFO: 128 bytes

Serial Signals

RS-232: TxD, RxD, RTS, CTS, DTR, DSR, DCD, GND

Driver Support

Operating Systems: Windows 9X/ME/NT/2000, Windows XP/2003/Vista/2008/7 x86/x64, Windows CE 5.0/6.0, Windows XP Embedded, DOS, Linux 2.4, Linux 2.6 x86/x64, QNX 6

Note: Please refer to Moxa's website for the latest driver support information.

Physical Characteristics

Dimensions: 90 x 96 mm (3.54 x 3.78 in)

Environmental Limits

Operating Temperature:

Standard Models: 0 to 55°C (32 to 131°F)

Wide Temp. Models: -40 to 85°C (-40 to 185°F)

Storage Temperature: -40 to 85°C (-40 to 185°F)

Ambient Relative Humidity: 5 to 95% (non-condensing)

Standards and Certifications

EMC: CE, FCC

EMI: EN 55022, EN 61000-3-2, EN 61000-3-3, FCC Part 15 Subpart B Class A

EMS: EN 55024, IEC 61000-6-2, IEC 61000-6-4, IEC 61000-4-2, IEC 61000-4-3, IEC 61000-4-4, IEC 61000-4-5, IEC 61000-4-6, IEC 61000-4-8, IEC 61000-4-11 (DIPS)

Green Product: RoHS, CRoHS, WEEE

MTBF (mean time between failures)

Time: 403,631 hrs

Database: Telcordia (Bellcore), GB

Power Requirements

Power Consumption: 153 mA @ 5 VDC

Warranty

Warranty Period: 5 years

Details: See www.moxa.com/warranty

: Ordering Information

Available Models

CB-108: 8-port RS-232 PC/104-Plus module, 0 to 55°C operating temperature

CB-108-T: 8-port RS-232 PC/104-Plus module, -40 to 85°C operating temperature

Connection Options (can be purchased separately)

CBL-F40M9x4-50: 40-pin box header to DB9 male x 4 connection cable, 50 cm

CBL-F40M25x4-50: 40-pin box header to DB25 male x 4 connection cable, 50 cm

Package Checklist

- 1 CB-108 or CB-108-T module
- Documentation and software CD
- Quick installation guide (printed)
- Warranty card