


# CB-134I Series

## 4-port RS-422/485 PC/104-Plus modules with 2 KV isolation



- > 921.6 Kbps maximum baudrate for super fast data transmission
- > On-chip S/W flow control
- > Built-in 15 KV ESD protection
- > Serial interface is DIP switch selectable
- > Onboard Tx and Rx LED indicators for each port
- > Windows XP/Vista/7, Windows CE 5.0/6.0, and Windows XP embedded operating systems supported
- > Wide temperature model available for -40 to 85°C environments



### : Overview

The CB-134I PC/104-Plus modules come with 4 RS-422/485 ports, and can be used with PC/104-Plus CPU boards that accept the PC/104-Plus expansion interface. Optional DB9 and DB25 connection cables are available for connecting to serial devices, and the CB-134Is'

versatile driver support makes the modules suitable for a wide range of applications. The CB-134I modules can be used on the PC/104-Plus (PCI) bus, and provide a reliable, high performance solution for multiport serial communication.

### : Specifications

#### Hardware

**Comm. Controller:** MU860 (16C550C compatible)  
**Bus:** PC/104-Plus bus  
**Connector:** 40-pin box header  
**DIP Switches:** Serial interface

#### Serial Interface

**Number of Ports:** 4  
**Serial Standards:** RS-422/485  
**Max. No. of Boards per PC:** 4

#### Serial Line Protection

**ESD Protection:** 15 KV on the board  
**Optical Isolation:** 2 KV

#### Performance

**Baudrate:** 50 bps to 921.6 Kbps

#### Serial Communication Parameters

**Data Bits:** 5, 6, 7, 8  
**Stop Bits:** 1, 1.5, 2  
**Parity:** None, Even, Odd, Space, Mark  
**I/O Address:** Assigned by BIOS  
**IRQ:** Assigned by BIOS  
**FIFO:** 128 bytes

#### Serial Signals

**RS-422:** TxD+(B), TxD-(A), RxD+(B), RxD-(A), GND  
**RS-485-4w:** TxD+(B), TxD-(A), RxD+(B), RxD-(A), GND  
**RS-485-2w:** Data+(B), Data-(A), GND

#### Driver Support

**Operating Systems:** Windows 9X/ME/NT/2000, Windows XP/2003/Vista/2008/7 x86/x64, Windows CE 5.0/6.0, Windows XP Embedded, DOS, Linux 2.4, Linux 2.6 x86/x64, QNX 6  
**Note:** Please refer to Moxa's website for the latest driver support information.

#### Physical Characteristics

**Dimensions:** 90 x 96 mm (3.54 x 3.78 in)

#### Environmental Limits

**Operating Temperature:**  
 Standard Models: 0 to 55°C (32 to 131°F)  
 Wide Temp. Models: -40 to 85°C (-40 to 185°F)  
**Storage Temperature:** -40 to 85°C (-40 to 185°F)  
**Ambient Relative Humidity:** 5 to 95% (non-condensing)

#### Standards and Certifications

**EMC:** CE, FCC  
**EMI:** EN 55022, EN 61000-3-2, EN 61000-3-3, FCC Part 15 Subpart B Class A  
**EMS:** EN 55024, IEC 61000-6-2, IEC 61000-6-4, IEC 61000-4-2, IEC 61000-4-3, IEC 61000-4-4, IEC 61000-4-5, IEC 61000-4-6, IEC 61000-4-8, IEC 61000-4-11 (DIPS)  
**Green Product:** RoHS, CRoHS, WEEE

#### MTBF (mean time between failures)

**Time:** 534,809 hrs  
**Database:** Telcordia (Bellcore), GB

#### Power Requirements

**Power Consumption:** 236 mA @ 5 VDC

#### Warranty

**Warranty Period:** 5 years  
**Details:** See [www.moxa.com/warranty](http://www.moxa.com/warranty)

### : Ordering Information

#### Available Models

**CB-134I:** 4-port RS-422/485 PC/104-Plus module with optical isolation protection, 0 to 55°C operating temperature  
**CB-134I-T:** 4-port RS-422/485 PC/104-Plus module with optical isolation protection, -40 to 85°C operating temperature

#### Connection Options (can be purchased separately)

**CBL-F40M9x4-50:** 40-pin box header to DB9 male x 4 connection cable, 50 cm  
**CBL-F40M25x4-50:** 40-pin box header to DB25 male x 4 connection cable, 50 cm

#### Package Checklist

- 1 CB-134I or CB-134I-T module
- Documentation and software CD
- Quick installation guide (printed)
- Warranty card