



# R2416600CB220 Rack Mount CCTV Power Supply

Rev. R2416600CB220\_10252012



R2416600CB220

## Overview

R2416600CB220 provides 24VAC or 28VAC distributed via sixteen (16) PTC protected outputs for powering CCTV cameras, heaters and other video accessories.

## Specifications

### **Input:**

- 220VAC, 50/60Hz, 3 amp.

### **Output:**

- Sixteen (16) PTC protected outputs.
- 24VAC @ 25 amp (600VA) supply current  
(1.5625 amp per device, 2.5 amp max.)
- or 28VAC @ 20 amp (560VA) supply current  
(1.25 amp per device, 2.5 amp max.).
- Outputs are rated @ 2.5 amp.
- Surge suppression.

### **Electrical:**

- Operating temperature: 0° C to 49° C ambient.
- BTU/Hr.:
  - 24VAC: 307.09 BTU/Hr.
  - 28VAC: 286.62 BTU/Hr.
- System AC input VA requirement: 660VA.

### **Features:**

- Sixteen (16) power LEDs.
- Illuminated master power disconnect circuit breaker with manual reset.
- 3-wire grounded line cord.
- Removable terminal blocks with locking screw flange.

### **Mechanical:**

- 2U rack mount chassis for use in standard EIA 19" rack.
- Enclosure Dimensions (H x W x D approx.):  
3.26" x 19.125" x 8.5" (83mm x 486mm x 216mm)
- Product weight (approx.): 22.7 lbs. (10.3 kg).
- Shipping weight (approx.): 24.0 lbs. (10.89 kg).

## Agency Approvals



European Conformity

**Enclosure Dimensions (H x W x D approximate):**  
 3.26" x 19.125" x 8.5" (83mm x 486mm x 216mm)

