

# TPM215-M2



Industrial monitor displays offer high-performance capacitive in industrial-grade LCD flat panels, with a 3mm thin flat surface. The touch screen LCD monitor is designed for indoor and outdoor application. The aluminum alloy closed enclosure, higher heat-dissipation than iron materials. IP65 rated dustproof and waterproof for the front panel.



# **Specification**

## Display

- LCD LED 21,5" 1920x1080dpi 16:9 aspect ratio
- Brightness: 350cd/m2 (1000cd/m2 optional)
- Contrast 800:1
- 50.000h MTBF backlight
- View angle: 85/85/80/80°
- Responds time: 5ms

## **Touch**

- 10-points PCAP touch Screen for finger
- Resolution 4096 x 4096
- Respond time <10ms

# I/O Interface

- RJ45 style USB Touchscreen interface (1,5m cable included)
- HDMI
- DVI
- VGA
- · Audio input and output
- 12-24V DC Input

## **Environmental**

- Operating temperature 0°C to +50°C
- Storage temperature -40°C to +85°C
- Humidity 5% to 90%

#### Mechanical

- IP65 protection for front panel
- Aluminum alloy enclosure and steel
- Panel mount Clip included.
- Measurements: 557x345x63mm
- Cut-out: 538,6x326,6mm

## Power

AC adapter 12V 4A, 100-240V, 50-60Hz

# Warranty

1 Year (standard)

## **Regulatory Approvals**

• CE, IP65 Front, RoHS, FCC

# **Options**

- No Touchscreen, Resistive Touchscreen
- Built-in Speakers
- DisplayPort
- High brightness 1000NITS
- Available in Silver color
- 12-36V low voltage DC input power

# **Order information**

• Model: TPM215-M2

P/N: 134033

